

MIXPLUS PA

Damp proof admixture for emulsions / renders

Mixplus PA is a liquid, admixture for emulsions, cems and renders which designed to prevent damp proof development in new structure and old structure as well. This is ready to add along with any emulsions products available in the market. This result in reduced drying shrinkage and less cracking. The reinforced Mixplus PA will act as a damp proof membrane after drying

Appropriation

Since improves workability and trowelling properties of enamels and cement renders during application and frost resistance for wide range of works like rendering / coating

Characteristics

Eliminates the need for lime
Improves moisture retention
Increase bond strength
Reduces shrinkage cracks and crazing
Improves weather resistance
Enables harsh sands
Eliminates efflorescence
Improves workability

Technical Data & Properties

Standard conforms: comply with ASTM C932
Appearance: White semi creamy
Specific gravity: 1.02 at 25°C
Air entertainment: 1- 2% according to dosage rates used
Chloride content: Nil, tested to BS5075
Freezing point: 0 °C. Mix prior to use
Flash point: None

Product Management

Mix proportions:
1ltr of Mixplus PA is sufficient for 3ltr emulsion

Mixing: Mixplus PA should be directly added to emulsions or maybe pre-mixed with the gauged water. Mechanical mixing should be employed where possible although thorough manual mixing may be acceptable for small batches if carried out vigourously

Effects of over dosage: Mixplus PA admixture will safeguard against over dosage by limiting the amount of air capable of being entrained. It is important to ascertain the reasons for the over dosage to avoid repetition

Packing & Storage

Mixplus PA is available in 5 litres and 20 litres drums. For site installations, deliveries will be made in bulk to site storage tanks. Mixplus PA should be stored in cool, shaded warehouses. Shelf life is 12 months

Health & Safety

Mixplus PA contains no hazardous substances. However, it should not be allowed to come into contact with skin and eyes. Wear suitable protective gloves and goggles whilst handling. When in contact with the skin and eyes wash thoroughly and immediate with warm water. If swallowed seek immediate medical attention. For more details, please refer to the MSDS released on each product.

MIXPLUS PA

Damp proof admixture for emulsions / renders

FAB

THE CONSTRUCTION CHEMIST

Technical information given in this datasheet is true and exact to the best of our knowledge, laboratory upshot and hands-on application. The datasheets of all products are revised/updated regularly and hence ensure that the latest release is used for reference and recommendation. The date of the publishing is as in this sheet. All data are mean of numerous tests, assessment and analysis conducted under laboratory ambiance. Climatic disparity in temperature, humidity, etc. and porosity of substrate may impinge on the values.

Group Head office:

PYCHEM Co. L L C
Post Box 23940, Sharjah.
Te: +971 6 5420414 / 5431636
Fax: +971 6 5421446
Mail: mail@fab-cc.com
fabchem@gmail.com

Under Technical Collaboration with
MIX UK Limited
Cherry Tree House, Cherry Tree Lane
Rostherne, Cheshire, WA143RZ
Web: www.mixuk.com

Head office:

T33A/1, Thryambhava Houses
Kalapetty road, Coimbatore – 14
Tel: 0422 3222245
Fax: 0422 2625207
Mail: mail@fab-cc.com
fabchem@gmail.com



FABCHEM



PYCHEM



MIX UK LTD